

Date : 1 Dec 2021

Our Ref: CD/FSSD/12/02/03/01

Registrar, Board of Architects Registrar, Professional Engineers Board President, Singapore Institute of Architects President, Institution of Engineers, Singapore President, Association of Consulting Engineers, Singapore

Dear Sir/Mdm,

ADVISORY ON INSTALLATION OF GATES/TURNSTILES IN BUILDINGS

Gates/turnstiles are commonly used in buildings for entry access control. Their installation affects the means of escape when installed along the egress path and shall be subjected to approval from SCDF as stipulated in Cl.2.3.1 of the Fire Code.

2 This circular serves to remind building industry stakeholders on the needs to ensure that any installation of gates/turnstiles along egress paths in buildings shall comply with the following guidelines:

a. Minimum width

The use of revolving turnstiles as access control is prohibited. Only non-revolving turnstiles and gate-type access control that flaps open or swings open in the direction of escape are permitted. Their minimum clear width shall be at least 460 mm.

b. Capacity of exits

Gates/turnstiles designated as exit facilities or installed across the path of main entrance or entry points that has been designated as exit facilities will be required to cater for the required exit capacity as stated in *Cl. 2.2.5*. See **Annex A** on example of possible layout for gates/turnstiles installation at main entrance of building.











SCDF – A member of the Home Team

HQ SINGAPORE CIVIL DEFENCE FORCE, 91UBI AVENUE 4, SINGAPORE 408827TEL: 6848 1457EMAIL: Tan_Chung_Yee@scdf.gov.sg

c. Determination of Travel distance

The maximum travel distance shall comply with Cl 2.2.6, taking into account the additional travel distance due to the gates/turnstiles installed along the escape route.

3. The content of this circular shall take immediate effect.

4. Please convey the contents of this circular to members of your Board/ Institution/ Association. This circular is also available in CORENET's e-Info: http://www.corenet.gov.sg/einfo.

5. For any inquiry or clarification, please contact LTC Tan Chung Yee at 68481457 or email address Tan_chung_yee@scdf.gov.sg.

Yours faithfully

(transmitted via email)

LTC Tan Chung Yee for Commissioner Singapore Civil Defence Force

Distribution list

CEO, BCA CEO, URA CEO, HDB CEO, JTC CE, LTA CE, Enterprise Singapore President, REDAS President, IFE President, SISV President, SISV President, SCAL Honorary Secretary, SPM Manager (Fire Safety & Building Control Unit), DSTA SCDF Fire Safety Standing Committee Fire Code Review Committee






SCDF – A member of the Home Team

HQ SINGAPORE CIVIL DEFENCE FORCE, 91 UBI AVENUE 4, SINGAPORE 408827

Annex A



Note:

1)Swing gate should linked to fire alarm if using EM locking otherwise it should always be openable and unobstructed during the occupancy of the building.

2)Turnstile with clear width more than 460mm

3)Swing gate to cater for equivalent exit capacity xx of designed exit











$\ensuremath{\textbf{SCDF}}\xspace - \ensuremath{\textbf{A}}\xspace$ member of the Home Team

HQ SINGAPORE CIVIL DEFENCE FORCE, 91 UBI AVENUE 4, SINGAPORE 408827